## 

## MRDS

The FAST<sup>™</sup> MRDS mount, in conjunction with the Optic Adapter Plates in the FAST<sup>™</sup> Modular Accessory Suite, brings compatible micro red dot sights to the established FAST<sup>™</sup> height of 2.26" to optical centerline. This includes micro red dot sights with any of the following footprints: RMR<sup>®</sup>, DeltaPoint<sup>®</sup> Pro, ACRO<sup>®</sup>, 509T, RMSc and Holosun<sup>™</sup> K. It comes standard with a two cross bolt rail clamp, but is compatible with the FAST<sup>™</sup> QD (Quick Detach) Lever. With exception to the Leupold<sup>®</sup> DeltaPoint<sup>®</sup> Pro, it is also compatible for use with the line of FAST<sup>™</sup> FTC magnifier mounts.

FAST<sup>™</sup> is a series of optic mounting solutions that provides end users with a quicker sight picture than standard height mounts. FAST<sup>™</sup> mounts position most optics at a 2.26" optical centerline from the rail, which allows for more rapid visual processing of the battlefield by ensuring an ergonomically correct heads-up posture. Further, they provide faster and easier dot/reticle acquisition while wearing night vision goggles, protective masks, plate carriers and other gear.





HEIGHT	COMPATIBILITY	RAIL MOUNT	WEIGHT	COLORS	
2.26" TO OPTICAL CENTERLINE	ALL OPTIC ADAPTER PLATES IN THE FAST™ MODULAR ACCESSORY SUITE	2 CROSS BOLT RAIL CLAMP, FAST™ QD LEVER COMPATIBLE	0Z: <3.0 G: <85.0	BLACK	FDE
				PART NUMBERS	
MATERIAL	COATING	DIMENSIONS (W X L X H)		BLACK	FST-MRDB
7075-T6 ALUMINUM	TYPE III HARDCOAT ANODIZED	IN: < 1.4 X 2.2 X 1.5 CM: < 3.5 X 5.5 X 3.8		FDE	FST-MRDF



## INFO@UNITYTACTICAL.COM

©2023 UNITY Tactical. All Rights Reserved. Specifications subject to change without notice. PAT: UTIP.CO



